

To: All customers and all distributors

Production discontinuation: SSEL-C/CS

August 2024

Dear Sir and Madam,

Thank you for being our valued customer. We appreciate your continued business and support.

Due to difficulty of continuing to produce the following models, we would like to announce herewith a production discontinuation.

- | | |
|-------------------------------|---|
| 1. Affected models | : SSEL-C/CS |
| 2. Reason for discontinuation | : Production discontinuation of the CPU used in this product |
| 3. Successor models | : RSEL + RCON-SC
Please see the next page for details. |
| 4. Order cutoff date | : 21. February 2025 |
| 5. Repair service cutoff date | : 21. February 2035
* We may have to stop service sooner, if the relevant parts are no longer available. |

We sincerely apologize for any inconvenience caused by the discontinuation of the products and ask for your understanding and cooperation.

Best regards,

IAI Industrieroboter GmbH
Ober der Röth 4
65824 Schwalbach am Taunus
Tel.: +49-6196-8895-0, Fax: +49-6196-8895-24
E-Mail: info@iai-automation.com Web: iai-automation.com

Differences between SSEL-C/CS and RSEL + RCON-SC

1. RSEL is not compatible with 100V AC power supply. 200V AC (single phase/3 phase) power supply is required.
2. 24V AC (1.2A or more) is needed as control power at gateway unit (RSEL-G).
3. If the actuator is equipped with absolute encoder (model: A) or multi-rotation absolute encoder (model: AM), or its motor power is below 60W, it cannot be connected to RSEL directly. The actuator needs to be connected to RSEL by using an extension unit (model: RCON-EXT) and SCON-C(G)B controller in RCON-EXT connection specification.
4. Product and mounting dimensions are different.
5. Due to the different connection form, the cables intended for SSEL-C cannot be connected to the connection for the RS232C interface (D-sub connection). As for the USB connection, RSEL has USB Mini-B while SSEL has USB Type-B.
6. Wiring for the power supply and emergency stop circuit are different.
7. Positioner mode of SSEL-C/CS is not supported by RSEL.
8. Old teaching pendants are not compatible with RSEL.
 - SEL-T and TB-01 are not compatible.
9. Parameter file and backup file are different.
 - XSEL PC software and TB-02/03 can convert position, program and symbol data of SSEL-C/CS to RSEL.
10. In case of direct connection to RCON-SC or connection via SCON2 controller, motor cable is different and must be changed. Please refer to the latest R-unit catalog for details.

Compatibility with RSEL + RCON-SC

- Serial communication via RS232C interface (D-sub connection) of SSEL-CS