

To: All customers and all distributors

Production-Discontinuation: TT series

February 2023

Dear Sir and Madam,

Thank you for being our valued customer. We appreciate your continued business and support.

Due to difficulty of continuing to produce the following models, we regret to announce herewith a production discontinuation.

- | | |
|-------------------------------|--|
| 1. Affected models | : all TT models |
| 2. Reason for discontinuation | : Difficult availability of the CPU and electric components used in this product and the availability of the successor model |
| 3. Successor models | : TTA series
Please find the next page for the detail. |
| 4. Order cutoff date | : 22 September 2023 |
| 5. Repair service cutoff date | : 23 September 2023
* We may have to stop the service earlier if the corresponding spare parts are no longer available. |

We sincerely apologize for any inconvenience caused by the discontinuation of the products and ask for your understanding and cooperation.

Best regards,

IAI Industrieroboter GmbH
Ober der Röth 4
65824 Schwalbach am Taunus
Tel.: +49-6196-8895-0, Fax: +49-6196-8895-24
E-Mail: info@iai-automation.com, Web: iai-automation.com

Differences between TT and TTA

1. Product and mounting dimension are different.
2. Different field network module: Field network configuration file needs to be changed.
3. More product variation and better specification in TTA: Strokes, number of axes, safety category compliance and pulse/servo motor
4. Different control specification
5. Parameter file and backup file are different
 - XSEL PC software and TB-01/02/03 can convert position, program and symbol data of TT to TTA.
6. Emergency stop circuit is different.
7. Different cable type on digital input/output (I/O)

Compatibility with TTA

- Serial communication via RS232C or USB interface
- Wiring for power supply